



Product	Name	Speaker Cable				
Conductor	Material	Copper Coated Aluminum			Electrical Characteristics (20°C)	Max. Conductor DC Resistance at 20°C (Ω/M) 0.019
	Nom. O.D. (mm)	2x30/0.25 (2x1.5mm <sup>2</sup> )	Up	+0.02		Rated Voltage (V) ≤36V
Jacket	External O.D.	3mm×2c	Up	+0.05	Sheath Physical Properties	Rated Temperature(°C) 70°C
			Down	-0.05		
	Surface	Smooth		View		
Material	PVC(complies RoHS Reach) CPR(Eca)		Drawn By		Page	

no.	Packaging	Length (m)	color
67720	Cable coil	10	transparent
67721	Cable coil	25	transparent
67722	Cable coil	50	transparent
15019	Cable Reel	100	transparent
67747	Cable coil	10	white
67748	Cable coil	25	white
67749	Cable coil	50	white
27523	Cable Reel	100	white
67732	Cable coil	10	red/black
67733	Cable coil	25	red/black
67734	Cable coil	50	red/black
15023	Cable Reel	100	red/black

Eca Fire class (CPR) according to DIN EN 13501-6

Änderungen			Datum	Name
Datum	Name	gez.:	12.08.2021	TL
12.08.2021	TL	gepr.:		
		Norm:		
Änderungen vorbehalten / Subject to change				

Bezeichnung	LSK 2x1,5mm <sup>2</sup>
Zeichnungs-Nr.:	27523 15019 15023 67749 67722 67734 67748 67721 67733 67747 67720 67732



Blatt	1/1
von	